

CELEBRATING FIVE DECADES OF ILLUMINATION

DAYMARK TM SURGICAL

HIGH-INTENSITY, PORTABLE LED SURGICAL HEADLIGHT WITH ADJUSTABLE SPOT. **POWERED BY A 4-CELL BATTERY**

- Illumination Range: ~60,000 LUX at 16" (40 cm) to ~260,000 LUX at 10" (25 cm)
- Adjustable Spot Diameter: 1"-4"(2.5 10.16 cm) at a working distance of 16" (40 cm)
- Color Temperature: 5,000 K
- Intensity Settings: 5 Levels
- 4-Cell Battery (System includes 2 batteries)
- Battery Duration at Full Intensity > 5 hours
- Battery Expected Life Span: > 300 Charges
- LED Expected Life Span: > 50,000 hours
- Optic Weight: 5 oz (141 g) • Battery Weight: 8.5 oz (240 g)







DAYMARK PORTABLE LED HEADLIGHT **SYSTEM INCLUDES:**

- Daymark Surgical Headlight on Fiji Headband
- Two 4-Cell Batteries
- Charging Cradle, Power Supply
- · Holster, Linkage Kit

DAYMARK PORTABLE LED HEADLIGHT SYSTEM PRODUCT CODES:

BFW 9070 Daymark Headlight System with Fiji Headband with Two 4-Cell Batteries

Daymark Protective Carrying Case, molded interior provides space for all components BFW 5440

BFW 9022ACC Daymark Mini Battery Charger BFW 9015 Daymark 4-Cell Battery BFW 9076 **Daymark Holster**

EXCELLENT FOR USE IN THE FOLLOWING DEPARTMENTS

HOSPITAL

ENT **GENERAL SURGERY** CARDIOSURGERY **NEUROSURGERY ORTHOPEDIC SURGERY** PEDIATRIC SURGERY SPINE SURGERY THORACIC SURGERY TRANSPLANT SURGERY VASCULAR SURGERY

SURGERY CENTER ORTHOPEDIC SURGERY PLASTIC SURGERY

DENTAL **OFFICE EXAM**

ORAL/MAXILLOFACIAL



BFWinc.com

800-717-4673 | +1-502-899-1808

2843 SAMCO ROAD, SUITE A

RAPID CITY, SD 57702 USA

ENGINEERED AND ASSEMBLED IN THE U.S.A. © 2024 BFW. Inc.

ALL TECHNICAL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

DAYMARK TESTED AND CERTIFIED TO: IEC 60601-1 Edition 3, IEC 60601-1-2 Edition 4, ANSI/AAMI ES60601-1 (2005 + C1:09 + A2:10), CAN/CSA C22.2 NO 60601-1 Edition 2 (2008), CE