



SEE BETTER
SEE FARTHER
SEE WHY






NEW! MAUI DOVER™

CORDLESS LED HEADLIGHT WITH FIXED SPOT, POWERED BY A HEADBAND MOUNTED BATTERY

- Illumination Range: ~30,000 LUX at 16" (40 cm) to ~105,000 LUX at 10" (25 cm)
- Fixed Spot Diameter: 3.5" (8.89 cm) at a working distance of 16" (40 cm)
- Color Temperature: 7,000K
- Intensity Controls Output from 0% to 100%
- Battery Expected Life Span: > 300 Charges
- LED Expected Life Span: > 50,000 hours
- Battery Run Time: 3 hours at full intensity,
- +1 hour of decreasing intensity
 Battery Charge Time: 3 hours
- Optic Weight: 0.45 oz (12.75 g)
- Battery Weight: 1.8 oz (51 g)
- Total Weight: 9.3 oz (263.65 g)





MAUI DOVER CORDLESS LED HEADLIGHT SYSTEM INCLUDES:

- Dover Optic on Maui Headband
- Two Mini Batteries
- Dual-Bay Charging Cradle, Power Supply
- Linkage Kit

MAUI DOVER CORDLESS LED HEADLIGHT PRODUCT CODES:

BFW 9030M Maui Dover Cordless Headlight System with Two Mini Batteries and Dual-Bay Charger

BFW 9035M Maui Dover Mini Battery

BFW 9023M Dual-Bay Charger with Wall Power Supply for USA, EU, UK, Canada, Mexico, Australia

BFW 9023MDPS Dual-Bay Desktop Charger with Power Supply for all other countries

BFW 5445 Protective Carrying Case

EXCELLENT FOR USE IN THE FOLLOWING DISCIPLINES

HOSPITAL

GENERAL SURGERY
CARDIOSURGERY
NEUROSURGERY
ORTHOPEDIC SURGERY
PEDIATRIC SURGERY
SPINE SURGERY
THORACIC SURGERY
TRANSPLANT SURGERY
VASCULAR SURGERY

SURGERY CENTER

ORTHOPEDIC SURGERY PLASTIC SURGERY

OFFICE

DENTAL EXAM

ORAL/MAXILLOFACIAL



BFWinc.com

800-717-4673 | +1-502-899-1808

2843 SAMCO ROAD, SUITE A

RAPID CITY, SD 57702 USA

ENGINEERED AND ASSEMBLED IN THE U.S.A. © 2024 BFW, Inc.

ALL TECHNICAL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

MAUI DOVER TESTED AND CERTIFIED TO: IEC 60601-1 EDITION 3, IEC 60601-1-2 EDITION 4, AAMI ES60601-1 EDITION 1, CSA C22.2 NO 60601-1:08 EDITION 2, CE